



Overview

Function	Print
----------	-------

Print

Speed (Mono)	Up to 33ppm in A4 (35ppm in Letter)
First Print Out Time (Mono)	Less than 8.5sec
Resolution	Up to 1200 x 1200dpi effective output
Duplex	Built-in
Emulation	PostScript3, PCL6, SPL, IBM ProPrinter, EPSON

Paper Handling

Media Size	76.0mm x 127.0mm (3" x 5") ~ 216.0mm x 356.0mm (8.5" x 14")
Media Type	Transparency, Envelope, Labels, Post Card, Card stock
Input Capacity and Types	250-sheet Cassette @ 80g/m ² , 50-sheet Multi Purpose Tray @ 80g/m ²
Output Capacity and Types	150-sheets @ 80g/m ² Face-Down

General

Processor	SAMSUNG 400MHz
Memory / Storage	64MB (Max. 320MB)

OS Compatibility	Windows 2000/XP(32/64bits)/Vista(32/64bits)/2003 Server(32/64bits) Various Linux OS: Red Hat 8 ~ 9, Fedora Core 1 ~ 4, Mandrake 9.2 ~ 10.1, SuSE 8.2 ~ 9.2 Mac OS 8.6 ~ 9.2, 10.1 ~ 10.4
Interface	Hi-Speed USB 2.0, IEEE1284 Parallel, Ethernet 10/100 Base TX
Noise Level	Less than 52dBA (Printing) Less than 26dBA (Standby)
Duty Cycles, Monthly	50000 sheets
Dimension (W x D x H)	400.0mm x 433.4mm x 285.0mm (15.75" x 17.1" x 11.2 ")
Weight	11.1kg (24.5lbs)

Consumables

Yield	Standard: Average Cartridge Yield 4K standard pages. High Yield: Average cartridge Yield 10K standard pages. Declared cartridge yield in accordance with ISO / IEC 19752.
Type	1-piece Cartridge
Model Code	ML-D3470A, ML-D3470B

Options

Options	250-sheet Cassette Tray-Memory: 32MB, 64MB, 128MB, 256MB
---------	--

※ Features and specifications are subject to change without prior notification.

Copyright© 2008 SAMSUNG. All rights reserved.